

Securing the Internet Routing: The Puzzle Pieces (revisited)

Tashi Phuntsho

tashi@nsrc.org



UNIVERSITY OF OREGON



Why BGP incidents?

Routing (still) works by RUMOUR

- TELL your neighbors what you know
- LEARN/accept what your neighbors know
- Assume everyone is *honest* (and correct)

Why BGP incidents?

NO one is in charge

- No single *authority* point for the Internet
- No *reference* point for what is *right* in routing

Routing is VARIABLE

- My view of the network depends on where I am
- No reference view to compare the local view against

Why BGP incidents?

We (still) don't have the E(evil) bit

- RFC3514



Puzzle Pieces: RFC8212

BGP is permissive by default (RFC4271):

- Without a policy, eBGP permits routes to be accepted and advertised
- AS-to-AS leaks happen

RFC8212 changes this (through code):

- From default Allow/Permit to default Deny/Reject
- For all eBGP sessions: Without an explicit import or export policy, DO NOT use routes received from, or send routes to eBGP peers.

Note: Does not stop applying a Permit ALL policy

Puzzle Pieces: RFC8212

<https://github.com/bgp/RFC8212> tracks implementations:

Default ON (Vendors)	• IOS-XR • SR OS (>19.5.R1) • SR Linux (>19.11.R1)
Default ON (Routing daemons)	• BIRD (>2.0.1) • OpenBGPD (>6.4) • FRR (>7.4)
Configurable knobs	• EOS (4.18.0f) • IOS-XE (17.2.1) • Junos (20.3R1)



Puzzle Pieces: WHOIS

At the very least, verify the resource holder:

```
whois -h whois.apnic.net 202.144.128.0/19
whois -h whois.apnic.net 2405:d000::/32

whois -h whois.apnic.net AS17660
whois -h whois.apnic.net AS18024
```

```
inetnum: 202.144.128.0 - 202.144.159.255
netname: BTTELECOM
descr: DrukNet, Bhutan Telecom
descr: Thimphu
country: BT
org: ORG-BTL2-AP
admin-c: JT106-AP
tech-c: JT106-AP
abuse-c: AB1276-AP
status: ALLOCATED PORTABLE
mnt-by: APNIC-HM
mnt-lower: MAINT-BT-DRUKNET
mnt-routes: MAINT-BT-DRUKNET
mnt-irt: IRT-BTTELECOM-BT
last-modified: 2020-10-20T01:02:25Z
source: APNIC
```

```
inet6num: 2405:d000::/32
netname: DRUKNET-BT-20080204
descr: Bhutan Telecom Ltd
descr: Internet Service Provider
country: BT
org: ORG-BTL2-AP
admin-c: JT106-AP
tech-c: JT106-AP
abuse-c: AB1276-AP
status: ALLOCATED PORTABLE
mnt-by: APNIC-HM
mnt-lower: MAINT-BT-DRUKNET
mnt-routes: MAINT-BT-DRUKNET
mnt-irt: IRT-BTTELECOM-BT
last-modified: 2021-01-14T06:16:00Z
source: APNIC
```

```
aut-num: AS17660
as-name: DRUKNET-AS
descr: DrukNet ISP
descr: Bhutan Telecom
descr: Thimphu
country: BT
import: from AS6461 action pref=100; accept ANY
export: to AS6461 announce AS-DRUKNET-TRANSIT
import: from AS2914 action pref=150; accept ANY
export: to AS2914 announce AS-DRUKNET-TRANSIT
```

```
aut-num: AS18024
as-name: BTTELECOM-AS-AP
descr: Bhutan Telecom Ltd
country: BT
org: ORG-BTL2-AP
admin-c: DN01-AP
tech-c: DN01-AP
abuse-c: AB1276-AP
mnt-lower: MAINT-BT-DRUKNET
mnt-routes: MAINT-BT-DRUKNET
mnt-by: APNIC-HM
mnt-irt: IRT-BTTELECOM-BT
last-modified: 2021-01-14T06:16:00Z
source: APNIC
```

Puzzle Pieces: IRR

Internet Routing Registry - IRR

- Where networks publish their routing intents
- ~ **route/route6** objects

```
route:      1.1.1.0/24
origin:     AS13335
descr:      APNIC Research and Development
             6 Cordelia St
mnt-by:     MAINT-APNICRANDNET
last-modified: 2023-04-26T02:42:44Z
source:     APNIC
```

```
route6:     2405:d000::/32
descr:      DRUKNET-IPV6-BLOCK
origin:     AS17660
notify:     netops@bt.bt
mnt-by:     MAINT-BT-DRUKNET
last-modified: 2010-07-21T03:46:02Z
source:     APNIC
```

Puzzle Pieces: IRR

Can be used to build route filters:

- With RPSL tools ([bgpq4](#))
- **Accept** (permit) if an entry exists in the IRR database

✓ Note the output diff when pointing to different sources

- bgpq4 defaults to [rr.ntt.net](#)

```
→ bgpq4 -bAl PEERv4-IN AS4608
PEERv4-IN = [
  103.246.136.0/22,
  110.76.136.0/22,
  202.12.29.0/24,
  203.30.127.0/24,
  203.119.76.0/23,
  203.119.92.0/23,
  203.119.92.0/24,
  203.119.96.0/20,
  203.119.100.0/22,
  203.119.104.0/21,
  203.133.248.0/23,
  203.133.248.0/24
];
```

```
→ bgpq4 -S APNIC -bAl PEERv4-IN AS4608
PEERv4-IN = [
  202.12.29.0/24,
  203.119.76.0/23,
  203.119.100.0/22,
  203.119.104.0/21,
  203.133.248.0/23,
  203.133.248.0/24
];
```

```
→ bgpq4 -6bAl PEERv6-IN AS4608
PEERv6-IN = [
  2001:dc0:2000::/35,
  2001:dc0:4000::/34{35,35},
  2001:dc0:8000::/34{35,35},
  2001:dc0:e000::/35,
  2001:dd8:8::/45,
  2001:dd8:8::/46{48,48},
  2001:dd8:c::/47{48,48},
  2001:dd8:f::/48,
  2001:df0:90::/48,
  2001:df2:ee00::/47{47,48},
  2401:2000::/32,
  2401:2000:6000::/35,
  2408:2000::/24
];
```

```
→ bgpq4 -S APNIC -6bAl PEERv6-IN AS4608
PEERv6-IN = [
  2001:dc0:2000::/35,
  2001:dc0:4000::/34{35,35},
  2001:dc0:8000::/34{35,35},
  2001:dc0:e000::/35,
  2001:dd8:8::/46{48,48},
  2001:dd8:c::/47{48,48},
  2001:dd8:f::/48,
  2001:df0:90::/48,
  2401:2000::/32,
  2401:2000:6000::/35,
  2408:2000::/24
];
```

Puzzle Pieces: IRR

Sometimes, transit provider relationships

(**as-set**) published too:

- To aggregate downstream networks, it maybe providing transit for

```
route:      X.1.2.0/24
origin:     AS18024

route6:     2001:db8:a::/48
origin:     AS18024
```

```
route:      X.1.3.0/24
origin:     AS18025

route6:     2001:db8:b::/48
origin:     AS18025
```

```
as-set:      AS17660:AS-DRUKNET
descr:       Druknet Internal & Transit Customers
tech-c:      DN01-AP
admin-c:     DN01-AP
mnt-by:      MAINT-BT-DRUKNET
members:     AS17660
members:     AS132232
members:     AS134715
members:     AS135666
members:     AS137925
members:     AS59219
members:     AS18024
members:     AS18025
members:     AS137994
members:     AS140695
members:     AS151498
members:     AS151955
members:     AS152317
members:     AS138558
members:     AS13335
members:     AS132894
members:     AS138529
members:     AS153779
members:     AS153740
members:     AS152480
members:     AS141680
members:     AS151782
notify:      netops@bt.bt
last-modified: 2026-08-06T08:56:47Z
source:      APNIC
```



Puzzle Pieces: IRR

AS-SET can be used to build:

- AS-PATH filters / prefix filters

```
bgpq4 -S APNIC -XA1 BTv4-IN AS17660:AS-DRUKNET
```

```
bgpq4 -Xf 17660 -l BT-AS-IN AS17660:AS-DRUKNET
```

```
→ bgpq4 -Xf 17660 -l BT-IN AS17660:AS-DRUKNET
as-path-set BT-IN
ios-regex '^17660(_17660)*$',
ios-regex '^17660(_[0-9]+)*_(13335|18024|18025|59219|132232|132894)$',
ios-regex '^17660(_[0-9]+)*_(134715|135666|137925|137994|138529|138558)$',
ios-regex '^17660(_[0-9]+)*_(140695|141680|151498|151782|151955|152317)$',
ios-regex '^17660(_[0-9]+)*_(152480|153740|153779)$'
end-set
```

```
→ bgpq4 -S APNIC -XA1 BTv4-IN AS17660:AS-DRUKNET
no prefix-set BTv4-IN
prefix-set BTv4-IN
1.0.0.0/24,
1.1.1.0/24,
1.32.192.0/18,
27.124.0.0/18,
36.50.37.0/24,
42.61.47.0/24,
43.226.16.0/21 ge 22 le 24,
43.226.124.0/22 le 24,
43.228.232.0/23 ge 24 le 24,
```

```
bgpq4 -S APNIC -6XA1 BTv6-IN AS17660:AS-DRUKNET
```

```
→ bgpq4 -S APNIC -6XA1 BTv6-IN AS17660:AS-DRUKNET
no prefix-set BTv6-IN
prefix-set BTv6-IN
2001:df0:eb80::/48,
2001:df2:a8c0::/48,
2001:df3:e180::/48,
2001:df4:3440::/48,
2001:df5:a300::/48,
2001:df5:acc0::/48,
2001:df5:d880::/47 le 48,
```



AS-SET Problems

- Cannot verify the integrity and authenticity of member ASNs
- No limit to the number of member ASNs ~ bloated AS-SETs

Example: the AS-SET called `AS9498:AS-BHARTI-IN` expands to:

<https://bgp.tools/as-set/as9498:as-bharti-in>

- 70,565 ASNs
- IPv4 prefixes: 1,962,411
- IPv6 prefixes: 1,275,055

[CIDR report](#) as of 27/08/2026:

- 79,361 ASNs (IPv4) | 37,376 ASNs (IPv6)
- IPv4 prefixes: 1,076,068
- IPv6 prefixes: 255,132

AS-SET Problems

Prevalence of non-hierarchical AS-SETs:

- Name collision

```
as-set: AS-GEMNET
descr: GEMNET s.r.o. ASes
members: AS59479
members: AS202733
tech-c: OK3789-RIPE
admin-c: OK3789-RIPE
mnt-by: GEMNETCZ-MNT
created: 2013-08-19T09:49:13Z
last-modified: 2024-08-27T14:09:27Z
source: RIPE
```

```
as-set: AS-GEMNET
descr: GEMNET LLC
country: MN
members: AS9934, AS9484, AS10219, AS9789,
AS38038, AS24496, AS24559, AS4850,
AS38042, AS38051, AS10076,
AS17882, AS38218, AS38454, AS38805,
AS38818, AS38273, AS10109, AS38869,
AS45237, AS45509, AS17463, AS24302,
AS45203, AS45204, AS45923, AS24320,
AS24496, AS45237, AS55342, AS55805,
AS55801, AS55408, AS55882, AS56194,
AS58598, AS58625, AS133177, AS135136,
AS138907, AS134074, AS45204:AS-GEMNET
tech-c: GA263-AP
admin-c: GA263-AP
mnt-by: MAINT-GEMNET-MN
mnt-lower: MAINT-GEMNET-MN
last-modified: 2024-10-08T02:49:37Z
source: APNIC
```



Non-hierarchical AS-SET: Bhutan

Only looking at the major transit ISPs:

AS17660:AS-DRUKNET

AS-NANO-ALL

AS38740:AS-TASHICELL

The next slide should help transition 😊

AS-SET Transition

1. Create a new hierarchical AS-SET

`AS17660:AS-DRUKNET` (same members as old one!)

2. Add the new AS-SET as member of the old one

`AS-DRUKNET-TRANSIT` [members: `AS17660:AS-DRUKNET`]

- From here on only update your new AS-SET

3. Inform your peers & update PeeringDB

- Ask your peers / providers to use your new AS-SET

4. Then delete the old AS-SET

```
as-set:      AS17660:AS-DRUKNET
descr:       Druknet Internal & Transit Customers
tech-c:      DN01-AP
admin-c:     DN01-AP
mnt-by:      MAINT-BT-DRUKNET
members:     AS17660
members:     AS132232
members:     AS134715
members:     AS135666
members:     AS137925
members:     AS59219
members:     AS18024
members:     AS18025
members:     AS137994
members:     AS140695
members:     AS151498
members:     AS151955
members:     AS152317
members:     AS138558
members:     AS13335
members:     AS132894
members:     AS138529
members:     AS153779
members:     AS153740
members:     AS152480
members:     AS141680
members:     AS151782
notify:      netops@bt.bt
last-modified: 2026-08-06T00:00:00Z
source:      APNIC
```

```
as-set:      AS-DRUKNET-TRANSIT
descr:       DrukNet transit networks
members:     AS17660
members:     AS132232
members:     AS134715
members:     AS135666
members:     AS137925
members:     AS59219
members:     AS18024
members:     AS18025
members:     AS137994
members:     AS140695
members:     AS151498
members:     AS151955
members:     AS152317
members:     AS138558
members:     AS13335
members:     AS132894
members:     AS138529
members:     AS153779
members:     AS153740
members:     AS152480
members:     AS141680
members:     AS17660:AS-DRUKNET
```

Puzzle Pieces: BGP Roles (RFC9234)

Defines a **ROLE** for your local AS with respect to your BGP neighbors:

– Roles:

- **Provider**: I provide transit to my neighbor
- **Customer**: I am customer of my neighbor
- **Peer**: We are peers
- **RS**: I am a route server
- **RS-client**: I am a client to a RS

– Allowed relationships:

- Provider <> Customer
- Customer <> Provider
- Peer <> Peer
- RS <> RS-client
- RS-client <> RS

Puzzle Pieces: BGP Roles (RFC9234)

Role capability negotiated through BGP open message

- Loose vs Strict

```
set protocols bgp group TRANSIT description 'My Transit Providers'  
set protocols bgp group TRANSIT otc-local-role customer  
set protocols bgp group TRANSIT neighbor 172.16.200.101 peer-as 64501
```

Configuring roles: Junos (>25.2R1)

```
router bgp 64522  
neighbor 172.16.200.101 remote-as 64501  
neighbor 172.16.200.101 description 'Transit from ISP-A'  
neighbor 172.16.200.101 local-role customer
```

Configuring roles: FRR



Puzzle Pieces: BGP Roles (RFC9234)

If role capability negotiated successfully:

- OTC (Only-to-Customer) attribute is exchanged
- User only sets the role: OTC works in code
- no OTC policy config needed 😊

OTC setting:

- Announcing
 - If a route is sent to Customer, Peer, RS-client set OTC attribute (ASN of the sender)
- Receiving:
 - If route is received from Provider, Peer, or an RS and OTC not set, mark with OTC attribute

```
✓ Border Gateway Protocol - UPDATE Message
  Marker: ffffffffffffffffffffffffffffffffff
  Length: 64
  Type: UPDATE Message (2)
  Withdrawn Routes Length: 0
  Total Path Attribute Length: 38
  ✓ Path attributes
    > Path Attribute - ORIGIN: IGP
    > Path Attribute - AS_PATH: 100 250
    > Path Attribute - NEXT_HOP: 100.100.3.1
    > Path Attribute - COMMUNITIES: 65000:0
    ✓ Path Attribute - OTC: 100
      > Flags: 0xc0, Optional, Transitive, Complete
      Type Code: OTC (35)
      Length: 4
      Only to Customer: 100
```



Puzzle Pieces: BGP Roles (RFC9234)

OTC Check:

– Outbound

- A route with OTC attribute **MUST NOT** be sent to **Provider, Peer, RS**

– Inbound

- If route with OTC is received from **Customer** or **RS-client**, it is a route leak. **Discard!**
- If a route with OTC received from a **Peer**, with a value other than its own ASN, it is a leak. **Discard!**

Puzzle Pieces: BGP Roles (RFC9234)

<https://blog.cloudflare.com/rfc9234-bgp-role-model/>

- Supported

- JunOS | Router OS | BIRD | OpenBGPD | FRR

- Announced

- IOS XR (in release 26.4.1)

- Not supported

- Arista EOS | SR OS | Huawei | SLX-OS | ArcOS | GoBGP | ExaBGP



Puzzle Pieces: RPKI [Origin Validation]


ROA – Route Origin Authorization

- Digitally signed ~ binds prefixes and nominated ASN
- Can be verified crypto-magically / chain of trust

Prefix	2001:DB8::/32
Max-length	/36
Origin ASN	AS64550

ROV – Route Origin Validation

- Helps validate if an ASN is permitted to originate a route
- Helps with mis-origination / origin hijack



Puzzle Pieces: RPKI [Origin Validation]


ROA – Route Origin Authorization

- Digitally signed ~ binds prefixes and nominated ASN
- Can be verified crypto-magically

Prefix	2001:DB8::/32
Origin	/36
Origin ASN	AS64550

ROV – Route Origin Validation

- Helps validate if an ASN is permitted to originate a route
- Mis-origination / origin hijack



Puzzle Pieces: RPKI [Origin Validation]

ROA Best Practices

- Minimal ROA (RFC9319):
 - ROA should only cover prefixes announced in BGP ~ use **maxLength** judiciously
- Multi ASN networks
 - More specific ROAs: Access ASNs
 - Aggregates and sub-aggregates: Transit ASN
- **AS0 ROA** (codified in RFC6483)
 - For unused/undelegated address space
 - **maxLength**: /32 v4 and /128 v6
 - April 2026 **Orange 90.98.0.0/15** hijack




...
A ROA with a subject of AS 0 (AS 0 ROA) is an attestation by the holder of a prefix that the prefix described in the ROA, and any more specific prefix, should not be used in a routing context.



Bhutan: ROA Status

Back to 100% ROA signed 😊 (first achieved in 2020)



<https://stats.labs.apnic.net/roa/BT>

```
→ monocle rpki validate AS153779 163.227.68.0/23
Data source: Cloudflare (cached at 2026-08-26 04:08:51 UTC, 994001 ROAs)
```

prefix	asn	state	reason
163.227.68.0/23	153779	valid	ROA exists with matching ASN and valid prefix length

Covering ROAs:

prefix	max_length	origin_asn	ta
163.227.68.0/23	24	153779	APNIC

```
→ monocle rpki validate AS0 2401:fe20::/32
Data source: Cloudflare (cached at 2026-08-26 04:08:51 UTC, 994001 ROAs)
```

prefix	asn	state	reason
2401:fe20::/32	0	valid	ROA exists with matching ASN and valid prefix length


Covering ROAs:

prefix	max_length	origin_asn	ta
2401:fe20::/32	32	0	APNIC

Bhutan: ROV Status

Difficult to see/measure:

- Maybe it is your transit provider (or their provider)
- APNIC Labs:
 - Global: 20%
 - Bhutan: ~ Only 34% of users cannot reach Invalid destinations
 - Only TashiCell doing validation



Source: <https://stats.labs.apnic.net/rpki>

ASN	AS Name	RPKI Validates ▼
AS137412	TASHICELL-MOBILE-AS - Tashicell Domestic AS Thimphu Bhutan	99.70%
AS23955	TASHICELL-DOMESTIC-AS - Tashi InfoComm Limited	89.66%

Puzzle Pieces: BGP "enforce First-AS"

During the April 2026 Orange incident:

- **AS0 ROA** would mark as Invalid | **ASPA** could detect the forged origin AS and forged AS_PATH
- But revealed lack of basic BGP sanity check ~ **first AS check/enforcement** by **AS199524** (and some well-known Tier-1s)

Spamhaus @spamhaus

We've recently observed some unusual large-scale routes appearing on the internet (see image), involving the following networks:

AS393232: Comcast Cable Communications 🇺🇸
AS36429: @chartercomms 🇺🇸
AS41128: @orange 🇫🇷
AS13335: @Cloudflare 🇺🇸
AS17072: @totalplaymx 🇲🇽
AS270118: SOLUCIONES, ANALITICOS Y SERVICIOS TEAM (Stratosphere Technology Latam) 🇲🇽
AS199524: @gcore_official 🇲🇽

The label "path (fixed)" indicates that identical paths were observed by several probes across the internet. This strongly suggests that AS199524 is the central pivot point behind these announcements.

While the first four paths have since disappeared, the most recent three remain active. ↓

Date	Prefix	Origin	Path (fixed)
2026-03-30	96.160.0.0/14	AS393232	AS17072 AS270118 AS199524
2026-03-30	96.164.0.0/14	AS393232	AS17072 AS270118 AS199524
2026-03-30	96.168.0.0/16	AS393232	AS17072 AS270118 AS199524
2026-03-30	96.188.0.0/14	AS393232	AS17072 AS270118 AS199524
2026-04-01	47.1.0.0/16	AS36429	AS13335 AS17072 AS270118 AS199524
2026-04-01	47.2.0.0/16	AS36429	AS13335 AS17072 AS270118 AS199524
2026-04-13	90.98.0.0/15	AS41128	AS17072 AS270118 AS199524

5:10 PM · Apr 13, 2026 · 75K Views

Rekhter, et al. Standards Track [Page 33]
RFC 4271 BGP-4 January 2006

If the UPDATE message is received from an external peer, the local system MAY check whether the leftmost (with respect to the position of octets in the protocol message) AS in the AS_PATH attribute is equal to the autonomous system number of the peer that sent the message. If the check determines this is not the case, the Error Subcode MUST be set to Malformed AS_PATH.

RFC 7606 Revised Error Handling for BGP August 2015

o It has a Path Segment Length field of zero.

An UPDATE message with a malformed AS_PATH attribute SHALL be handled using the approach of "treat-as-withdraw".

[RFC4271] also says that an implementation optionally "MAY check whether the leftmost ... AS in the AS_PATH attribute is equal to the autonomous system number of the peer that sent the message". A BGP implementation SHOULD also handle routes that violate this check using "treat-as-withdraw" but MAY follow the "session reset" behavior if configured to do so.

Routes to be removed from Adj-RIB-In

Puzzle Pieces: BGP “enforce First-AS”

<https://blog.cloudflare.com/enforce-first-as-bgp/> revealed:

Networks:

- Enforce ‘first AS’ check:

- AS174 | AS1299 | AS3257 | AS3491 | AS5511 | AS6453 | AS7018

- Did **NOT** enforce:

- AS701 | AS2914 | AS3356 | AS6461 | AS6762 | AS6830 | AS12956

Vendors:

- JunOS | SR OS | RouterOS | SLX-OS | BIRD did **NOT** enforce ‘first AS’ by default!
- available as configuration knobs (except RouterOS)

2026-06-03



Bryton Herdes



Bryce Walters



Mingwei Zhang

1. Allocated two IP prefixes, one for IPv4 and one for IPv6, to advertise to Tier 1 External BGP (EBGP) neighbours
2. Purposely prepended the test prefix advertisements to Tier 1 neighbours with a Cloudflare-owned, non-13335 ASN (AS402542) in front of 13335



UNIVERSITY OF OREGON



Puzzle Pieces: RPKI [Path Validation]

ASPA – Autonomous System Provider Authorization

- Binds a set of Provider ASNs to a Customer ASN
 - signed by the holder of the Customer ASN
- (Re)uses existing tool chains - **No crypto** on routers!

```
→ monocle rpki aspas --customer 4608 --format markdown
Data source: Cloudflare (cached at 2026-08-26 04:08:51 UTC, 2782 ASPAs)
Found 1 ASPAs
```

Customer ASN	Customer Name	Country	Providers
AS4608	Asia Pacific Netw...	AU	1221, 4826, 7575

```
→ monocle rpki aspas --customer 1299 --format markdown
Data source: Cloudflare (cached at 2026-08-26 04:08:51 UTC, 2782 ASPAs)
Found 1 ASPAs
```

Customer ASN	Customer Name	Country	Providers
AS1299	f/k/a Telia Carrier	SE	0



AS0 ~ I have no transit providers!



Puzzle Pieces: ASPA

APNIC **ASPA Signer/Dashboard** available ~ June 2026

– Shout out to Tom Harrison and the Registry team @APNIC



Be careful:

- Verify what is seen in BGP before import!
- You should know who your upstreams are.
- Include any non-transparent Route Server AS(es)

Screenshots Credit: Dr. Philip Smith

Puzzle Pieces: ASPA


AS-to-AS hop verification (Upstream: Customer to Provider)

At each hop, look at the customer AS, check if the next AS is listed as one of its providers in the ASPA data

- If every hop in the path lines up, path is **VALID (Provider)**
- If any hop contradicts ASPA data (a customer AS says “this AS is not my provider”), path is **INVALID**
- If for one or more hops in the path, there is no ASPA data – it is **Unknown (No Attestation)**

Puzzle Pieces: ASPA

ASPA: spoofed origin AS



<https://github.com/APNIC-net/rpki-rtr-demo>

– AS1 announce 192.168.1.0/24 (ROA exists)

– ASPA:

AS1 > [AS2]

AS2 > [AS3]

AS3 > [AS0]

AS4 > [AS3]

– AS4 sees:

5 1 192.168.1.0/24

3 2 1 192.168.1.0/24

– AS4 checks ASPA

- AS5 is 'Not Provider' for AS1

– Hence, INVALID

Puzzle Pieces: ASPA

ASPA can find valleys (detect leaks):


Take the longest possible:

- Customer to Provider path from the origin as UP ramp
- Provider to Customer on the reverse end as DOWN ramp

UP and DOWN must either:


- Meet at adjacent peers
- Meet at a shared provider
- Overlap with multiple hops

A gap in the UP and DOWN indicates there is a valley - **Invalid**



Puzzle Pieces: ASPA

ASPA: Provide to Provider leak



<https://github.com/APNIC-net/rpki-rtr-demo>

– AS1, announce 192.168.1.0/24 (ROA exists)

– ASPA:

AS1 > [AS2]

AS2 > [AS3]

AS4 > [AS3, AS5] – two upstreams

AS6 > [AS5]

AS3 > [AS0] and AS5 > [AS0]

– AS6 sees: 5 4 3 2 1 192.168.1.0/24

- ASPA says: AS4 is 'Not Provider' for AS3

- UP: 3 2 1 (from origin) – 2 hops

- ASPA says: AS4 is 'Not Provider' for AS5

- DOWN: 6 5 (AS6 verifying) – 1 hop

- There is a gap (UP/DOWN don't cover the full AS_PATH)

– AS4 is a valley → INVALID



ASPA Timeline: as of August 2026

	Available Now	Announced / Underway	TBC
Standards		RTRv2 and ASPA Both still in draft – maybe end of 2026?	
Signers	– ARIN – RIPE – APNIC		– AfrinIC – LACNIC
RP	– Routinator (RP + RTR) – rpkiclient (RP) – RTRTR (RTR proxy & server) – FORT – Krill (delegated CA)		
Vendor BGP		– Nokia: SROS R27 ~ 2027 – JunOS: 26.4 (Q4 2026) – Cisco: IOS-XR 27.1?	– Huawei: NetEngine? – Arista?
Routing Daemons	– OpenBGPD (>7.8) – BIRD		



Summary

RFC8212: No policy? No routes!

Enforce-first-as:

- Did I receive the update from my actual neighbour?
- Watch out for transparent AS peers (route servers)

ROA/ROV: Is this ASN allowed to originate this prefix?

BGP Roles: am I allowed to advertise this route to this neighbour?

ASPA: Is the AS_PATH consistent with authorised providers?



Questions?



UNIVERSITY OF OREGON

